



## Delta AC Slim II (Cordset)

### Key Features

- Compact, stylish design
- Up to 16A / 230V / 3.6kW charging
- -40°C to +50°C wide operating temperature range
- IP67 protection

### Applications



Parking  
space



Commercial



Fleet

Power Input	Input Rating	200-240Vac (or 100-120Vac) single phase, max. 16A, 50 Hz / 60Hz
	Input Plug Type	Subject to region or country standards
Power Output	Output Rating	200-240Vac (or 100-120Vac) single phase, max. 16A, 50 Hz / 60Hz
	Charging Interface	IEC 62196-2 Type 1(SAE J1772), IEC 62196-2 Type 2 or GB/T plug
	Electrical Protection	Over current, Under voltage, Over voltage, Residual current, Surge protection, Short circuit, Over temperature, Ground fault
User Interface & Control	Status Indicators	AC Present, Charging, Over Temperature, Fault
Environmental	Operating Temperature	-40 °C to +50 °C
	Storage Temperature	-40 °C to +85 °C
	Humidity	< 95% relative humidity, non-condensing
	Altitude	Up to 2000 m
Mechanical	Ingress Protection	IP67, excluding plug and cable
	Cooling	Natural cooling
	Dimension (W x H x D) / Weight	152 x 76 x 40 mm / 600 g, excluding plug and cable
Regulation	Certificate / Compliance	UL, PSE, CE Subject to region or country standards

Specifications are subject to change without notice.

### Delta Electronics, Inc.

3 Tungyuan Road, Chungli Industrial Zone,  
Taoyuan City 32063, Taiwan  
TEL : +886-3-4526107  
FAX : +886-3-4527314

For more product information and sales inquiries,

Please contact [evcs@deltaww.com](mailto:evcs@deltaww.com)

[www.deltaww.com/evcs](http://www.deltaww.com/evcs)

