

# DPS 2900 Series

## DC Power System



DPS 2900 Series is the power system playing the leader role in Telecom industry and Data center application with 300A of the power for 48V system. It is modular, expandable and can be easily installed in 19-inch enclosure, also with high cost-performance ratio and gorgeous efficiency all rolled into one, that is, your one of a kind energy core.

To maintain all aspects of the power performance, working perfectly at extremely high efficiency up to 96.4% and keeping low consumption, not to mention the ultra-leading power density, makes DPS 2900 Series the extraordinary green design and the savior of reducing CO<sub>2</sub>.

Relying on the advanced real time monitoring mechanism and comprehensive battery management, ensuring prevention before problems and lengthening the battery life can reach each component's full potential in a compact 6U shelf and generate savings in OPEX.

### Key Features

- Leading Efficiency 96.4%
- Perfect Integration with Delta Outdoor Enclosure
- Compact Design 19" 6U System
- Remote Monitoring Interface
- Battery Management System

### Applications

- 3G / 4G / 5G
- Fixed Line
- Datacom



# DPS 2900 Series



GOAQEE-00-ZL

## INPUT

Voltage	Single phase; 220 - 240V <sub>AC</sub> , 103A (Max.); 3W (L, N, PE) Three phase; 346 - 415V <sub>AC</sub> / 200 - 240V <sub>AC</sub> , 34.3A (Max.); 5W (L1, L2, L3, N, PE)
Frequency	50 / 60Hz ±5%

## OUTPUT

Voltage (nominal)	-48V <sub>DC</sub>
Voltage (default)	-54V <sub>DC</sub>
Voltage (adjustable range)	-42 to -58V <sub>DC</sub>
Maximum Power @ nominal Input	17.4kW

## MECHANICAL

Dimensions (W x H x D)	485 x 264 x 347mm (19 x 13.7 x 25.4in)
Weight	approx. 18kg (39.68lb) (without rectifier)

## ENVIRONMENTAL

Operating Temperature	0 to +65 °C (32 to +149 °F)
Storage Temperature	-40 to +75 °C (-40 to +167 °F)
Altitude	-152 to +3048m
Related Humidity	0 - 95%, non-condensing
Acoustic Noise	< 65dBA

## STANDARDS

Environment	RoHS
-------------	------

\* All specifications are subject to change without prior notice.

**Delta Electronics Inc.**  
3 Tungyuan Road, Chungli Industrial Zone,  
Taoyuan City 32063, Taiwan.  
T +886 3 452 6107 / F +886 3 452 7314  
[www.deltaww.com](http://www.deltaww.com)

